

PerformaTech™

Top tier performance commercial double glazing

We believe that light and comfort should go hand-in-hand. That's why we created PerformaTech™.

PerformaTech™ balances high levels of light transmission with very low levels of solar heat gain to provide you with a brighter and more comfortable space.

**Turn over to learn about the product range,
performance and benefits.**



For more information on PerformaTech™
visit www.viridianglass.com
or contact 1800 847 434.

Viridian 
we ♥ glass™

With exceptional light transmission, solar control, and thermal insulation - PerformaTech™ enables specifiers, developers, architects, and engineers alike, the opportunity to create truly inspirational, economically viable and environmentally sustainable buildings.

Reducing energy consumption in every aspect of our lives is fast becoming an increasing priority. In response to this concern industry code changes have focused on increasing commercial building efficiency, which can often sacrifice valuable visible light needed for a healthy living and working environment. With a new generation of Low-E coating, PerformaTech™ products provide the balance between energy management and aesthetics that you've been looking for.

Product Benefits:



- Superior insulation with the inclusion of a soft coat Low E coating.
- Allows you to better manage window to wall ratio to balance thermal and daylight requirements.
- A range of toned options available to meet aesthetic requirements.



- Can be customised to support design or acoustic requirements if required.
- Very high performance available in clear options.



- Processed in Australia.



- Ten year warranty from date of manufacture.

Product Range and Performance:

Outside Glass	Inside Glass	Nominal Thickness (mm)	VLT	U-Value	SHGC
PerformaTech™ Range					
PerformaTech™ PH08	VFloat™ Clear	6+12+6	68	1.3	0.33
PerformaTech™ PH20	VFloat™ Clear	6+12+6	46	1.3	0.19
PerformaTech™ PH25	VFloat™ Clear	6+12+6	59	1.3	0.25
PerformaTech™ PH30	VFloat™ Clear	6+12+6	68	1.3	0.29
VFloat™ Light Grey	PerformaTech™ PH30	6+12+6	47	1.3	0.29
VFloat™ Grey	PerformaTech™ PH30	6+12+6	32	1.3	0.23
VFloat™ Green	PerformaTech™ PH30	6+12+6	58	1.3	0.31
VFloat™ Bronze	PerformaTech™ PH30	6+12+6	39	1.3	0.26

The assembly of this product is protected.
 Typical measured values of Viridian production are provided.
 All performance data is determined using LBL window 7.5 software. NFRC 100 - 2010 conditions have been used.
 Glass surfaces are counted from the exterior to the interior of the building.

For more information on PerformaTech™
 visit www.viridianglass.com
 or contact 1800 847 434.

